

Instruction Manual of Fire Alarm sound

(model : LW5609)

Product Function:

When receiving fire alarm host control signal, The fire alarm sound device sends out strong voice alarm signal, remind the field personnel to pay attention to!

Executive Standard: GA385-2002

Technical features:

Item	Parameters
Operating voltage	DC24V (+10%、 -15%)
Operating current	≤20mA
Dimensions	Φ152mm
Sound pressure level (A)	75~115db
Environment temperature	-10°C~50°C
Environment humidity	≤95%RH

(Version:20111128)

Instruction Manual of Fire Alarm sound

(model : LW5609)

Product Function:

When receiving fire alarm host control signal, The fire alarm sound device sends out strong voice alarm signal, remind the field personnel to pay attention to!

Executive Standard: GA385-2002

Technical features:

Item	Parameters
Operating voltage	DC24V (+10%、 -15%)
Operating current	≤20mA
Dimensions	Φ152mm
Sound pressure level (A)	75~115db
Environment temperature	-10°C~50°C
Environment humidity	≤95%RH

(Version:20111128)

Instruction Manual of Fire Alarm sound

(model : LW5609)

Product Function:

When receiving fire alarm host control signal, The fire alarm sound device sends out strong voice alarm signal, remind the field personnel to pay attention to!

Executive Standard: GA385-2002

Technical features:

Item	Parameters
Operating voltage	DC24V (+10%、 -15%)
Operating current	≤20mA
Dimensions	Φ152mm
Sound pressure level (A)	75~115db
Environment temperature	-10°C~50°C
Environment humidity	≤95%RH

(Version:20111128)

Instruction Manual of Fire Alarm sound

(model : LW5609)

Product Function:

When receiving fire alarm host control signal, The fire alarm sound device sends out strong voice alarm signal, remind the field personnel to pay attention to!

Executive Standard: GA385-2002

Technical features:

Item	Parameters
Operating voltage	DC24V (+10%、 -15%)
Operating current	≤20mA
Dimensions	Φ152mm
Sound pressure level (A)	75~115db
Environment temperature	-10°C~50°C
Environment humidity	≤95%RH

(Version:20111128)